

**Listing of Claims:**

Claims 1-9 (Cancelled)

10. (Currently amended) A roof window comprising a window frame having an inner surface, a sash frame, and a covering, each of the window frame and the sash frame including a top frame member, a horizontally-extending bottom frame member and two lateral frame members, said roof window comprising drainage grooves, characterized in that a first drainage groove is formed in the window frame, and a second drainage groove is formed in the sash frame, wherein the window frame has an inner surface adjacent to the sash frame, wherein the sash frame has an outer surface adjacent to the window frame, wherein the first drainage groove has a concave surface extending along the inner surface of the window frame and formed with a flange protruding from the inner surface of the window frame, wherein the second drainage groove has a concave surface extending along the outer surface of the sash frame, and includes a flange protruding from the outer surface of the sash frame, wherein the first drainage groove formed in the inner surface of the window frame constitutes a complex drainage channel for the window frame, while the second drainage groove formed in the outer surface of the sash frame constitutes a complex drainage channel for the sash frame, and wherein the complex drainage channel for the window frame comprises the first drainage groove formed with the lateral and bottom members of the window frame, while the complex drainage channel for the sash frame comprises the second drainage groove formed with the lateral and bottom members of the sash frame, wherein the flange of the second drainage groove in the lateral frame members of the sash is spaced horizontally from the inner surface of the window frame, and wherein the complex drainage channel for the window sash has a drainage exit.

Claims 11 - 13 (Cancelled)

14. (Previously presented) A roof window according to claim 10, further comprising a top surface on the window frame flange and a bottom surface on the sash frame flange, a first sealing surface on the top surface of the window frame flange, and a second sealing surface on the bottom surface of the sash frame flange, with a sealing element sandwiched between the first and second sealing surfaces, wherein the drainage groove of the window frame is located correspondingly underneath the drainage groove of the sash frame, with the first sealing surface facing the second sealing surface, so that water overflowing from the sash frame drainage groove goes into the window frame drainage groove.

15. (Previously presented) A roof window according to claim 10, wherein the first drainage groove has a surface in each of the lateral frame members of the window frame, wherein the first drainage groove has a surface in the top frame member of the window frame, wherein the second drainage groove has a surface in each of the lateral frame members of the sash frame, the flange of the sash frame has a top surface, a cross section of the second drainage groove surface in each of the lateral frame members of the sash frame comprises a portion of the outer surface of the sash frame and a portion of the top surface of the flange of the sash frame, wherein the cross section of the second drainage groove surface of the top frame member of the sash frame comprises a portion of the outer wall surface of the sash frame and a portion of the top surface of the flange of the sash frame, wherein the top surface of the flange of the sash frame is flat, wherein the bottom frame member of the window frame has an inner surface

provided with a separate reservoir for receiving rain, dew and condensate, wherein the separate reservoir has a flat bottom surface ending with a flange formed with the inner surface of the bottom frame member of the window frame, wherein the top surface of the flange formed with the inner surface defines a sealing surface facing a corresponding sealing surface defined on the bottom frame member of the sash frame, with a sealing element sandwiched between the sealing surfaces, and wherein the separate reservoir ends with the flanges of the drainage grooves of the lateral frame members of the window frame.

16. (Currently amended) A roof window comprising a window frame having an inner surface, a sash frame, and a covering, each of the window frame and the sash frame including a top frame member, a bottom frame member and two lateral frame members, said roof window comprising drainage grooves, characterized in that a first drainage groove is formed in the window frame, and a second drainage groove is formed in the sash frame, wherein the window frame has an inner surface adjacent to the sash frame, wherein the sash frame has an outer surface adjacent to the window frame, wherein the first drainage groove has a concave surface extending along the inner surface of the window frame and formed with a flange protruding from the inner surface of the window frame, wherein the second drainage groove has a concave surface extending along the outer surface of the sash frame, and includes a flange protruding from the outer surface of the sash frame, wherein the first drainage groove formed in the inner surface of the window frame constitutes a complex drainage channel for the window frame, while the second drainage groove formed in the outer surface of the sash frame constitutes a complex drainage channel for the sash frame, and wherein the complex drainage channel for the window frame comprises the first drainage groove formed with the lateral and bottom members

of the window frame, while the complex drainage channel for the sash frame comprises the second drainage groove formed with the lateral and bottom members of the sash frame ~~A roof window according to claim 10~~, wherein the bottom frame member of the sash frame has a top surface, a horizontal drainage groove is positioned on the top surface of the bottom frame member of the sash frame and communicates with exits placed at both ends of the lateral frame members of the sash frame, wherein a portion of the covering is a bottom frame covering, a mounting groove is formed in the bottom frame member of the window frame, with an end of the bottom frame covering positioned in said mounting groove, whereby drainage water from the window frame can be discharged from the covering, wherein the drainage groove of the lateral frame members of the sash frame extends to the top surface of the bottom frame member of the sash frame, from which the drainage water can be discharged.

17. (Currently amended) A roof window comprising a window frame having an inner surface, a sash frame, and a covering, each of the window frame and the sash frame including a top frame member, a bottom frame member and two lateral frame members, said roof window comprising drainage grooves, characterized in that a first drainage groove is formed in the window frame, and a second drainage groove is formed in the sash frame, wherein the window frame has an inner surface adjacent to the sash frame, wherein the sash frame has an outer surface adjacent to the window frame, wherein the first drainage groove has a concave surface extending along the inner surface of the window frame and formed with a flange protruding from the inner surface of the window frame, wherein the second drainage groove has a concave surface extending along the outer surface of the sash frame, and includes a flange protruding from the outer surface of the sash frame, wherein the first drainage groove formed in the inner

surface of the window frame constitutes a complex drainage channel for the window frame,  
while the second drainage groove formed in the outer surface of the sash frame constitutes a  
complex drainage channel for the sash frame, and wherein the complex drainage channel for the  
window frame comprises the first drainage groove formed with the lateral and bottom members  
of the window frame, while the complex drainage channel for the sash frame comprises the  
second drainage groove formed with the lateral and bottom members of the sash frame A-roof  
~~window according to claim 10,~~ wherein the bottom frame member of the sash frame has a top  
surface, wherein the first drainage groove formed in the window frame has a lower end portion  
having a width which is reduced as the position for measuring the width approaches the bottom  
member of the window frame, wherein the second drainage groove has lower end portions on the  
lateral frame members of the sash frame, wherein the lower end portions have a curvature  
upwardly towards the top surface of the bottom frame member of the sash frame, and wherein  
the lower end portions of the second drainage groove have a width which is reduced as the  
position for measuring the width approaches the bottom member of the window frame.

18. (Previously presented) A roof window according to claim 15, wherein the top  
surface of the flange of the sash frame is inwardly inclined down.

19. – 25. (Cancelled)